



### GANTRAIL 3120/15/35 Clip

- 1 Rail
- 2 Gantrail MKII pad
- 3 Gantrail 3120/15/40/ clip
- 4 Epoxy or cementitious grout
- 5 Steel sole plate
- 6 Nut and set screw for levelling\*
- 7 M20 hold down bolt grade 4.6
- 8 Bolt grout

\* Several alternative leveling methods are available. Please refer to Gantry Railing for more information

Rail	Origin	A mm	F mm	C mm	Kg/m	B mm	D mm	E mm	G mm	K mm	M mm	Q mm	W mm
BS113A	U.K.	159	140	64	56.8	166	15**	***	165	****	214	116	287
S54	GERMANY	154	125	70	54.5	161	15**	***	165	****	199	111	272
104lb	U.S.A.	127	127	64	51.6	134	15**	***	165	****	201	84	274
135lb	U.S.A.	146	132	87	67.0	153	15**	***	165	****	206	103	279
MRS87A	LUXEMBOURG	152	152	102	86.8	159	15**	***	165	****	226	109	299
ISCR80	INDIA	130	130	87	64.2	137	15**	***	165	****	204	87	277
68kg AREA	AUSTRALIA	186	152	73	67.7	193	15**	***	165	****	226	148	299

\*\* 15mm typical - Gantrail can advise for specific applications

\*\*\* Dimension 'E' is determined by the application and the type of grout used.

\*\*\*\* Dimension 'K' is usually between 600mm and 900mm for most applications. This dimension varies depending on factors such as wheel load and usage. Gantry Railing can provide calculations to determine this dimension subject to availability of critical data.

**Note:** Rails listed are those most commonly used with the 3120/15/40 clip. For compatibility with other rails, inquiries should be made direct to Gantry Railing Limited

## GANTRY RAILING LIMITED

International crane rail mounting specialists

NOT FOR DISTRIBUTION IN NORTH AMERICA AND CANADA



# GANTRAIL®